

# CAPACITIES

Year	Model	Engine		Transmission			Transfer Case (pts.)	Drive Axle		Fuel Tank (gal.)	Cooling System (qts.)	
		Displacement Liters (cc)	Engine ID/VIN	Engine Oil with Filter	4-Spd.	5-Spd. (pts.)		Auto.	Front (pts.)			Rear (pts.)
		1997	Cherokee	2.5 (2458)	P	4.0	—	6.6 ⑧	17.0	3.0 ⑥	3.1	3.5 ⑨
		4.0 (3996)	S	6.0	—	6.6	17.0	3.0 ⑥	3.1	3.5 ⑨	20.2	12.0
	Grand Cherokee	4.0 (3996)	S	6.0	—	6.5	17.0	3.2 ⑦	3.1	3.4	23.0	12.0
		5.2 (5211)	Y	5.0	—	6.5	19.5	3.2 ⑦	3.1	3.4	23.0	14.9
		5.9 (5899)	Z	5.0	—	—	⑩	⑪	2.5	⑫	23.0	14.9
	Wrangler	2.5 (2458)	P	4.0	—	6.6	17.5	⑬	3.7	3.5	⑭	9.0
		4.0 (3996)	S	6.0	—	6.6	17.5	⑬	3.7	3.5	⑭	10.5
1998	Cherokee	2.5 (2458)	P	4.0	—	6.6 ⑧	17.0	3.0 ⑥	3.1	3.5 ⑨	20.2	10.0
		4.0 (3996)	S	6.0	—	6.6	17.0	3.0 ⑥	3.1	3.5 ⑨	20.2	12.0
	Grand Cherokee	4.0 (3996)	S	6.0	—	—	⑩	⑪	3.1	⑫	⑩	12.0
		5.2 (5211)	Y	5.0	—	—	⑩	⑪	3.1	⑫	23.0	14.9
		5.9 (5899)	Z	5.0	—	—	⑩	⑪	2.5	⑫	23.0	14.9
	Wrangler	2.5 (2458)	P	4.0	—	6.6	17.5	⑬	3.7	3.5	⑭	9.0
		4.0 (3996)	S	6.0	—	6.6	17.5	⑬	3.7	3.5	⑭	10.5
1999-00	Cherokee	2.5 (2458)	P	4.0	—	6.6 ⑧	17.0	3.0 ⑥	3.1	3.5 ⑬	20.2	10.0
		4.0 (3996)	S	6.0	—	6.6	17.0	3.0 ⑥	3.1	3.5 ⑬	20.2	12.0
	Grand Cherokee	4.0 (3996)	S	6.0	—	—	⑩	⑪	3.1	⑫	⑩	12.0
		4.7 (4701)	N	6.0	—	—	⑩	⑪	2.5	⑫	20.5	13.0
	Wrangler	2.5 (2458)	P	4.0	—	6.6	17.5	⑬	3.7	3.5	⑭	9.0
		4.0 (3996)	S	6.0	—	6.6	17.5	⑬	3.7	3.5	⑭	10.5

① Asian Warner: 7.4 pts.

② Optional: 20 gal.

③ Heavy Duty: 3.0 pts.

④ 2WD: 7.4 pts.

⑤ Long Bed: 23.5 gal.

⑥ Command-Trac - 2.2 pts.

⑦ NP242: 2.9 pts.

NP249: 2.5 pts.

⑧ 2WD - 7.0 pts.

⑨ 8 1/4 axle: 4.4 pts.

When equipped with TRAC-LOK,

include 2 oz. of friction modifier additive

⑩ 42RE: 19-22 pts.

44RE: 19-22 pts.

45RFE: 28.0 pts.

46RE: 19.5-28.0 pts.

⑪ 242 NVG: 3.0 pts.

247 NVG: 2.5 pts.

249 NVG: 2.5 pts.

⑫ 194 RBI: 3.5 pts.

198 RBI: 3.75 pts.

216 RBA: 4.75 pts.

226 RBA: 4.75 pts.

If equipped with VARI-LOCK or TRAC-LOCK,

include approx. 0.25 pt. of Friction Modifier.

⑬ Command-Trac:

Automatic: 2.2 pts.

Manual: 3.3 pts.

⑭ Standard: 15.0 gals.

Optional: 19.6 gals.