

CRANKSHAFT AND CONNECTING ROD SPECIFICATIONS

All measurements are given in inches.

Year	Engine Displacement Liters (cc)	Engine ID/VIN	Crankshaft				Connecting Rod		
			Main Brg. Journal Dia.	Main Brg. Oil Clearance	Shaft End-play	Thrust on No.	Journal Diameter	Oil Clearance	Side Clearance
1990	2.5 (2458)	E	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	2	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
	4.0 (3982)	L	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	3	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
	4.2 (4227)	M	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	3	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
	5.9 (5899)	7	2.7474-2.7589 ①	0.0010-0.0030 ②	0.0030-0.0080	3	2.0934-2.0955	0.0010-0.0025	0.0060-0.0180
1991	2.5 (2458)	P	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	2	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
	4.0 (3996)	S	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	3	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
	5.9 (5899)	7	2.7474-2.7589 ①	0.0010-0.0030 ②	0.0030-0.0080	3	2.0934-2.0955	0.0010-0.0025	0.0060-0.0180
1992	2.5 (2458)	P	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	2	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
	4.0 (3996)	S	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	3	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
1993	2.5 (2458)	P	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	2	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
	4.0 (3996)	S	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	3	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
	5.2 (5211)	Y	2.4996-2.5001 ③	0.0010-0.0025 ④	0.0020-0.0100	3	2.1240-2.1250	0.0005-0.0022	0.0060-0.0140
1994	2.5 (2458)	P	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	2	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
	4.0 (3996)	S	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	3	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
	5.2 (5211)	Y	2.4996-2.5001 ③	0.0010-0.0025 ④	0.0020-0.0100	3	2.1240-2.1250	0.0005-0.0022	0.0060-0.0140
1995	2.5 (2458)	P	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	2	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
	4.0 (3996)	S	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	3	2.0934-2.0955	0.0010-0.0025	0.0100-0.0190
	5.2 (5211)	Y	2.4996-2.5001 ③	0.0010-0.0025 ④	0.0020-0.0100	3	2.1240-2.1250	0.0005-0.0022	0.0060-0.0140
1996	2.5 (2458)	P	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	2	2.0934-2.0955	0.0015-0.0020	0.0100-0.0190
	4.0 (3996)	S	2.4996-2.5001 ③	0.0010-0.0025	0.0015-0.0065	3	2.0934-2.0955	0.0015-0.0020	0.0100-0.0190
	5.2 (5211)	Y	2.4995-2.5005	0.0005-0.0015	0.0020-0.0070	3	2.1240-2.1250	0.0005-0.0022	0.0060-0.0140
	5.9 (5899)	Z	2.8095-2.8105	0.0005-0.0015	0.0020-0.0070	3	2.1240-2.1250	0.0005-0.0022	0.0060-0.0140
1997	2.5 (2458)	P	2.4996-2.5001	0.0010-0.0025	0.0015-0.0065	2	2.0934-2.0955	0.0015-0.0020	0.0100-0.0190
	4.0 (3996)	S	2.4996-2.5001 ③	0.001-0.0025	0.0015-0.0065	3	2.0934-2.0955	0.0015-0.0020	0.0100-0.0190
	5.2 (5211)	Y	2.4995-2.5005	0.0005-0.0015	0.0020-0.0070	3	2.1240-2.1250	0.0005-0.0022	0.0060-0.0140
	5.9 (5899)	Z	2.8095-2.8105	0.0005-0.0015	0.0020-0.0070	3	2.1240-2.1250	0.0005-0.0022	0.0060-0.0140